

## XT4131A – Portable Industrial IP54 Thermal Printer Bluetooth/WiFi



Specifications	XT4131A Description
Print method	Direct thermal line
Printer head	SEIKO(Original)
Resolution	203DPI (384dots/line)
Print speed	40-60mm/s
Character set	ASCII, GB18030 (Chinese), BIG5 (support French, English, etc.)
Effective printing width	72MM
Print font	12x24, 9x17, Chinese:24x24
Character per line	48-font A / 64-font B
Bar code	<b>1D:</b> UPC-A, UPC-C, EAN-13, EAN-8, CODE39, ITF25, CODEBAR, CODE93, CODE128 - <b>2D:</b> PDF417, QR CODE, DATA Matrix
Graphics	Support bitmap image and logo printing
Memory Printing	YES
Paper End Sensor	YES
Overheating Protection	YES
Interface	USB + Bluetooth / WiFi / RS-232 (Call Spark for correct models)
Emulation	ESC/POS; SDK; CPCL
Driver	Windows 7/8/10/XP
Running OS	Windows Mobile, WinCe, Android, IOS
Screen	OLCD, Menu Support Chinese and English
Power saving	Auto power saving and 1 second wake up – Standby 150 hours
Working Time each charge	150 to 180 meters with 12,5% printer density
Detecting	Double black label detect
Battery	Battery 7.4V Li-polymer (2000 mAh) – Recharge Time: 2 or 3 hours
Charging	Charger 100~240V AC 50-60Hz / Car-Charger (optional)
Dimension (LxWxH)	125mm X 106mm(D) X 55mm
Net weight	436G
Gross weight	900G
Paper type	Thermal paper/Thermal label
Paper width	MAX 79.5± 0.5mm
Paper roll diameter	MAX 40M (Receipt paper length 26m)
Roll core inner diameter	13mm (min)
Paper thickness	0.05mm ----0.15mm
Paper loading	Drop in paper loading
Operating Temp/Humidity	-10°C / 50°C 10%-80%
Storage Temp/Humidity	-10°C / 60°C 10%-90%
Certification	CCC, CE, ROHS, IP54
Protections	Pass 1.2 meters anti-dropping test / IP54 = Waterproof and Dustproof
Application	Logistic, warehouses, Convenience Stores, Retails, Super markets, Financial